



Corokap EV

Vent element of the eaves

A vent element made of high quality PVC. It does not deform under the pressure of a roof coverage. It protects the eaves area against contamination intrusion. It is also resistant to different weather conditions and UV-rays. Special construction of bottom part of the product allow the easy installation of gutters' hooks.

Advantages

- ✓ increased ventilation space
- ✓ protects eaves' area against access of birds, rodents
- ✓ provides great air-circulation of the roof space



Application

- ✓ as an element of ventilation and protection of open eaves space in case of tile roofing and other flat tiles

Characteristics

| | |
|---|--|
| Material | PVC |
| Colour | black, brown, brick red |
| Length | 1000 mm |
| Height | 32 mm |
| Vicat softening temperature | ≥ 70°C |
| Tensile strength | ≥ 26 MPa |
| Relative elongation at break | ≥ 5,5 % |
| Dimensional and shape stability at temp. over a period of 3 h, change in dimensions | ≤ 1,0 no defects, no shape changes |

Installation

1. Place eaves closing comb on the support batten, and then fix it.
2. Install the next batten on which the tiles are mounted so that the tile enters the gutter between 1/4 and 1/2 of its width.

The product has passed a positive assessment of its performance for the intended use: ventilation and roofing. Confirmation document: National Technical Assessment No. ITB-KOT-2020/1462 edition 1.

Storage

The product should be stored in dry and covered places, protected against deformations. Transport it by covered means of transport, adequately protecting against damage.

Packaging

| | |
|----------------------------------|------|
| Quantity per box (pcs.): | 100 |
| Quantity on a pallet (box./pcs): | 1200 |

The information contained in this data sheet, particularly recommendations regarding the manner and conditions of application as well as the scope of use of the product, have been developed based on our experience, our best knowledge and in good faith. Apart from the information given in this data sheet, health and safety regulations, etc. must be observed. This technical data sheet supersedes all previous versions applicable to this product.