

Corotop® FLEX

ENG/TAS/CFX/042017
AKT/12.04.2017

Description	Tape for ventilation systems
Material	Polypropylene sprayed with aluminium
Adhesive	Acrylic
Properties	The polipropylene single-sided adhesive tape covered with aluminium. It protects against moisture and solvent penetration. It is resistant to UV-rays and ageing processes.
Application	Adhesion in systems of ventilation, air conditioning, and heating
Advantages	<ul style="list-style-type: none"> • good adherence properties • isolates vapour and moisture • universal- to be used on both smooth and rough surfaces

Technical Data

Length [m]	50
Width [mm]	50; 75
Thickness [mm]	0,051
Breaking resistance	100 N/25mm
Elongation to break	140%
Adhesion to steel	5.0 N/25mm
Color	Silver
Temperature resistance	od + 10°C do +80°C
Package	36 (50mm); 24 (75mm)
Per pallet [pcs]	2592 (50mm); 1728 (75mm)
Pallet dimensions	1200 x 800 x 1600
Product weight [kg]	0,15 (50mm); 0,20 (75mm)
Pallet weight [kg]	415 (50mm); 370 (75mm)
Barcode	5903364600327 - 50mm
	5903364602178 - 75mm

Assembly and storage

How to use/ Assembly instructions	The tape should be pressed to a dry, contaminant-free surface.
Conditions of use and storage	Conditions of use and storage Products should be stored in a dry place (humidity up to 70%) at temperatures above 10°C.

Photo



Label	 tasma aluminiowa	
	Szerokość / Width / Breite / Ширина / Šírka 50 mm Długość / Length / Länge / Длина / Délka 50 mb Ilość / Quantity / Menge / Количество / Množství 36 szt.	<p>Agencja techniczna: Korona Serwis i Inżynieria ul. Włocławek 21 15-007 2014</p>  5 910 3 3 8 4 16 0 0 3 2 7
www.corotop.com		

The information, recommendations and hints have been provided in good faith on the basis of our best knowledge, research and experience. We assume no responsibility for effects of improper or invalid use of our products. Every user of this material has to ascertain, using all possible means, including checking of the end products under the proper conditions, of usability of the materials delivered for the defined purpose.

Product information can be found on the Web page www.corotop.com.pl