



# Corotop MIX

## Double-sided tape for bonding membranes

Double-sided adhesive tape for bonding vapour barrier films, roofing membranes and other construction products based on plastics. Made of polyester mesh coated on both sides with a special adhesive based on acrylic dispersion. Resistant to UV radiation and ageing processes.

### Advantages

- ✓ excellent adhesive properties
- ✓ universal: on both smooth and rough surfaces
- ✓ resistant to different weather conditions

### Application

- ✓ for bonding and fixing the polypropylene and polyethylene plastic foils
- ✓ for connecting foil with plastics, concrete, wood and metal



### Characteristics

Material	mesh from polyester fibre, acrylic dispersion	Peel strength of joints	≥25 N /25 mm
Colour	transparent white	Elongation	100 %
Length	25 or 50 m	Temperature of application	+10°C to 30°C
Width	20 or 40 mm	Temperature resistance	-30°C to 100°C
Thickness	0,22 – 0,24 mm		

### Installation

- 1 Clean the surface from dust and other contamination.
2. Do not tighten the tape on the bonding surface.
3. Observe the recommended temperature for using.

### Storage

The product should be stored in the manufacturer's original packaging, in dry, covered areas. The product should be transported in covered means of transport, secured against damage.

### Packaging

Quantity per box (pcs.):	12 (20 mm), 7 (40 mm)
Quantity on a pallet (box./pcs):	60/720 (20 mm) 60/420 (40 mm)

The information contained in this data sheet, particularly recommendations regarding the manner and conditions of application as well as the scope of use of the product, have been developed based on our experience, our best knowledge and in good faith. Apart from the information given in this data sheet, health and safety regulations, etc. must be observed. This technical data sheet supersedes all previous versions applicable to this product.