

Corotop UV

Single-sided tape for bonding membranes

The multiseasonal single-sided adhesive tape. It is produced from the acrylic dispersion reinforced with polyester fibres to have better adhesiveness properties. Made of polypropylene coated with a special adhesive based on acrylic dispersion. Resistant up to 24 month to UV radiation and ageing processes. Perfect for partly open façades

Advantages

- ✓ 24 month outdoor exposure
- ✓ high bonding strength
- ✓ extensible
- ✓ high weather resistance

Application

- ✓ for partly open façades
- ✓ for bonding and fixing the polypropylene and polyethylene plastic foils
- ✓ for connecting foil with plastics, concrete, wood and metal
- ✓ to be used inside building structures



Characteristics

Material	LDPE, polyester mesh, acrylic adhesive - EC1Plus	Peel strength of joints	≥35 N /25 mm
Colour	black	Elongation	100 %
Length	25 m	Temperature of application	from -10°C
Width	60 mm	Temperature resistance	-40°C to +100°C
Thickness (without liner)	0,30 mm		

Installation

1. Clean the surface from dust and other contamination.
2. Do not tighten the tape on the bonding surface.
3. Observe the recommended temperature for using.

Storage

The product should be stored in the manufacturer's original packaging, in dry, covered areas. The product should be transported in covered means of transport, secured against damage. Storage at 15-25 °C with rH 40 - 60%.

Packaging

Quantity per box (pcs.):	5
Quantity on a pallet (box./pcs):	175/875