

Corovent PRO

Ridge and hip sealing tape

Sealing and ventilation tape made of two strips of profiled aluminium laminate, glass fibre fabric and butyl adhesive strips. It provides very efficient ventilation, while protecting against precipitation and insects.

Advantages

- ✓ extremely high UV resistance
- ✓ provides efficient ventilation of the roofing
- ✓ resistant to biological corrosion
- ✓ specially profiled edges of the tape ensure effective connection to the coating

Application

- ✓ for the protection and ventilation of ridges and hip pitched roofs



Characteristics

Material	aluminium, glass fabric, butyl
Colour	anthracite, black, brick,
Length	5 m
Width	310 mm
Adhesive layer width	25 mm
Joining strength: Shear strength tape,	
- tape - clay roofing tile	
- tape - cement tile	≥140(N/50mm)
- strip - galvanized steel sheet	≥150(N/50mm)
	≥150(N/50mm)
Nominal thickness of the paint film	7 μm
Temperature resistance	-40°C to +80°C

The product has passed a positive assessment of its performance for the intended use: ventilation and roofing. Confirmation document: National Technical Assessment No. ITB-KOT-2020/1462 edition 1.

Storage

Store the product in its original packaging in a protected, dry and clean place away from heat sources and sunlight.

Installation

1. Unroll the product directly on the ridge patch and then attach to the ridge patch (e.g. staples).
2. The edges of the ridge tape should be correctly profiled and then sealed to the tiles with butyl adhesive strips on the edges of the ridge tape.
3. The substrate (tiles) should be cleaned before bonding.
4. The works should be conducted at temperature >5°C.
5. If it is necessary to connect two ridge tapes, an overlap of min. 75 mm.

Packaging

Quantity per box (pcs.):	8
Quantity on a pallet (pcs):	288