



## DECLARATION OF PERFORMANCE No. 266-CPR-2026

1. Unique identification code:

Bituminous membrane for pitched roofs

### NEXLER Optimax PRO PV (2026/1)

2. Intended use or uses:

- layer for regulating water vapor permeation subject to reaction to fire testing
- layer for regulating water vapor permeation.

3. The manufacturer:

**NEXLER Sp. z o.o.**  
ul. Łużycka 6, 81-537 Gdynia, Poland  
tel., fax +48 58 781 45 85  
e-mail: [info@nexler.com](mailto:info@nexler.com)

4. Systems of assessment and verification of constancy of performance:

**system 3 – for the applications: a, b**

5. Harmonized standard:

EN 13859-1:2010

Notified body or notified bodies:

1434 Polish Centre for Testing and Certification (Polskie Centrum Badań i Certyfikacji S.A.)

6. Declared performance:

Essential characteristics	Performance	Harmonized technical specification according to point 5 of DoP
Reaction to fire	Class F	EN 13859-1:2010
Resistance to water permeation	Class W1	
Maximum tensile force: - longitudinal - extension	600 ± 200 N/50 mm (45 ± 15) %	
- transversal - extension	400 ± 200 N/50 mm (45 ± 15) %	
Resistance to tearing: - longitudinal - transversal	300 ± 150 N 300 ± 150 N	
Elasticity at low temperature (flexibility)	≤ -25 °C	
Durability after artificial ageing related to:  - mechanical properties:  maximum tensile properties: - longitudinal - transversal  elongation: - longitudinal - transversal  - resistance to water permeation	  NPD  NPD  NPD	

The performances of the product identified above are consistent with a set of declared performance. This declaration of performance is issued in accordance with Regulation (EU) no 305/2011 the sole responsibility of the producer referred to above.

Signed on behalf of the manufacturer:

Konrad Liberda

Kierownik Biura Produkcyjnej  
Wspierania Technicznego  
Konrad Liberda

in Gdynia, on 12.01.2026

